

1 REFLECTED CEILING PLAN

LIGHT FIXTURE SCHEDULE

TYPE	MANUFACTURER	CATALOG NO.	WATTAGE	REMARKS	TYPE	MANUFACTURER	CATALOG NO.	WATTAGE	REMARKS
B2 (OPTION 1)	LSI SECURITY	BESA CIERRO TYPE P4 "RUBBY MATTE" (1 PENDANT FIXTURE)	GU-24	DECORATIVE GLASS SINGLE PENDANT LIGHT. PENDANTS TO BE CENTERED OVER TABLES. HEIGHTS VARY. LOWEST BOTTOM OF LIGHT: 6'-6" A.F.F. AT DINING TABLE.	J	HERMITAGE-SECURITY	SL-LED 48-DO-120-BL-ADJ	50	1.4' LINEAR LED GOOSE NECK EXTERIOR FIXTURE MARKED FOR WET LOCATION. TO BE MOUNTED ON 12" ARM 2. COLOR TO MATCH EXISTING FIXTURES
B2 (OPTION 2)	TREND LIGHTING	BKP-003 W/ BULBLED	60W	DECORATIVE PENDANT LIGHT WITH PENDANTS TO BE CENTERED OVER TABLES PER DECOR DRAWINGS. COORDINATE LOCATION AND QUANTITY WITH DECOR SUPPLIERS BOTTOM OF LIGHT @ 6'-6" A.F.F.	K (REMODELS)	LSI SECURITY	XS12-S-LED-50-CW-120-WHT-CMT (RETROFIT)	62	EXTERIOR DROP DOWN SOFFIT LIGHT (MANSARD)
D	LSI SECURITY	PDL6-LED-HO-WW-120-SD	14	6" OR 7" DIAMETER RECESSED LED DOWN LIGHT	L	LSI SECURITY	XPWWS3-FI-LED-48-450-CW-UE-MSV RS-30WLED-DO-SV-120 (DOWN ONLY) RWSC-30LED-WD-PS-MT (UP/DOWN ONLY) RWSC-30LED-UD-PS-MT (UP/DOWN ONLY)	53 30 30	
D2		BY G.C.		LED WALL WASHER	M	KONTECHUSA	KON-WS-40-XX (DOWN ONLY) KON-WS-60-XX (UP/DOWN)	40 60	TO BE USED AT AWNINGS ONLY
E	LSI SECURITY	PEC14-LED-HO-RED-WW-UE	34	1x4 RECESSED LED	N	LSI SECURITY	XGBWM3-WT-LED-48-450-CW-UE-MSV	53	WALL MOUNTED SECURITY LIGHT
G	LSI SECURITY	GA24-LED-HO-NW-UE-P12	57	2x4 RECESSED LED (REQUIRED TO BE USED IN KITCHEN)	EM	LSI SECURITY	LTEM-WH	(2) 1 LED	EMERGENCY LIGHT
C	SECURITY	SLSF5741-31MOGU241SLED	15	6" DIAMETER SURFACE MOUNTED	EMX	SECURITY	PRX-R-UJ-WH-WH-PR50-R12	(2) 1.1 LED	EXIT/EMERGENCY LIGHT
	CREE (RUUD)-HERMITAGE	LLT1430LWGFA12FE-C388	26.4			CREE (RUUD)-HERMITAGE	PGM3-30LU-5K-PS	69	
	CREE (RUUD)-HERMITAGE	ZR14-40L-35K-10V	44			CREE (RUUD)-HERMITAGE	E.WF1X03127	27	
	CREE (RUUD)-HERMITAGE	CR24-40L-35K-S	45			LSI SECURITY	PE 6		
	CREE (RUUD)-HERMITAGE	LR6-10L-30K-120-A-DR W/SC6-BK-GU24 W/ LT6	11			CREE (RUUD)-HERMITAGE	EMP22WH		

- ### GENERAL NOTES
- ALL DIMENSIONS SHOWN ON REFLECTED CEILING PLAN ARE FROM FACE OF WALL FINISH UNLESS NOTED OTHERWISE.
  - THE REFERENCE HEIGHTS INDICATED ON PLAN ARE FROM APPROXIMATE FINISH FLOOR (A.F.F.)
  - CONTRACTOR SHALL VERIFY FIXTURE QUANTITIES AND ALSO MAKE PROPER ADJUSTMENTS FOR ANY CHANGES IN PLAN DUE TO ADDITIONAL REQUIREMENTS, LOCAL CODES, ETC.
  - ALL FIXTURES SHALL BE LOCATED IN THE CENTER OF CEILING TILES UNLESS NOTED OTHERWISE.
  - DINING ROOMS ARE DESIGNED TO A 35-40 FOOT CANDLE LEVEL. KITCHENS ARE DESIGNED TO A 75 FOOT CANDLE LEVEL. RESTROOMS ARE DESIGNED TO A 50 FOOT CANDLE LEVEL.
  - PROJECT SPECIFIC TYPES AND QUANTITIES.
  - PENDANT FIXTURES "B2" MUST BE CENTERED OVER TABLE TOPS. COORDINATE WITH DECOR DRAWINGS.
  - EXCEPT FOR DROPPED CEILING OPTION, ALL LIGHT FIXTURES IN DINING ROOM AREA AND RESTROOM CORRIDOR ARE TO BE SUPPORTED FROM EXPOSED ROOF TRUSSES. USE 2x4 BETWEEN BOTTOM CORDS FOR SURFACE MOUNTED FIXTURES.
  - SEE INTERIOR DECOR PLAN FOR PENDANT LIGHT PLACEMENT.
  - GC TO PROVIDE DUPLEX OUTLET EVERY 12'-0" @ WINDOW FACE. MAX. 18" FROM TOP OF WINDOW.

### CEILING SPECIFICATIONS



<b>ACT-1L</b>	FINE FISSURED #1732
LOCATION:	DINING
MANUFACTURER:	ARMSTRONG
COLOR:	ADOBE
GRID:	2X2 ANGLED REGULAR 15/16
DIMENSION:	2'X2'X3/4"
CONTACT:	ARMSTRONG STRATEGIC ACCOUNTS (800.442.4212)
<b>ACT-2L</b>	#BP670 ENVIROWALL
LOCATION:	SERVICE AISLE/BACK OF HOUSE
MANUFACTURER:	ARMSTRONG
COLOR:	WHITE
GRID:	PRELUDE 15/16" EXPOSED TEE GRID
DIMENSION:	2'X4'X1/2"
CONTACT:	ARMSTRONG STRATEGIC ACCOUNTS (800.442.4212)
<b>P-3L</b>	PAINTED GYPSUM BOARD CEILING

- ### SCOPE OF WORK PROPOSED
- A100** REPLACE HVAC GRILLES, DIFFUSERS AND THERMOSTATS.
  - A101** REPLACE DINING RM AND SERVICE AISLE CEILING GRID & TILE
  - A102** REPAIR AND CLEAN BOH CEILING GRID AND REPLACE TILES.
  - A103** REPLACE EXISTING EXIT/EMERGENCY LIGHTS (EMX) (EM) WITH NEW AS PER SPECIFICATION. REFER TO LAYOUT FOR LOCATIONS.
  - A104** INSTALL 2020 PENDANT LIGHTS AS PER DECOR DRAWINGS AND SPECIFICATION.
  - A105** INSTALL NEW LED RECESSED LIGHTS IN DINING ROOM.
  - A106** REPLACE RESTROOM EXHAUST FANS AS NEEDED AS PER SPEC.
  - A107** INSTALL NEW LIGHT FIXTURES IN RESTROOMS PER LAYOUT.
  - A108** INSTALL NEW CANOPIES, INCLUDING LIGHTING AS PER SPECIFICATIONS, REFERENCE A-2/A-6/A-7 FOR DETAILS & SIZES.
  - A109** PAINT RESTROOM GYPSUM CEILING AS PER 2020 DECOR PACKAGE REQ. REPAIR CEILING AS NECESSARY FOR NEW LAYOUT.
  - A110** INSTALL FLAT SCREEN TELEVISION AS PER DECOR DRAWINGS, G.C. TO PROVIDE POWER.
  - A111** REPLACE BOH LIGHTING TO NEW LED 2X4 LIGHTS 1:1.
  - A112** REPLACE LIGHTING ON EXISTING MANSARD ONE FOR ONE.
  - A113** EXTEND DRIVE THRU SOFFIT TO MATCH NEW BUMP OUTS.

### SYMBOLS LEGEND

SYMBOL	DESCRIPTION
	SUPPLY AIR DIFFUSERS (ALUMINUM TO MATCH CEILING COLOR)
	RETURN AIR GRILLES (ALUMINUM TO MATCH CEILING COLOR)
	EXHAUST FAN GRILLES (ALUMINUM TO MATCH CEILING COLOR)

No.	Date	By	Notes
1	6/8/16	JW	SUBMITTED TO CITY
2	6/22/16	CG	REVISION 1
Drawn By: PM			
Checked: SB			
Scale: AS NOTED			
Date: 04.01.16			



PROJECT	BURGER KING #5743 3100 GRATIOT AVE. MARYSVILLE, MI	SHEET TITLE	REFLECTED CEILING PLAN
JOB #	TG-16353	DO NOT SCALE THIS PRINT. USE FIGURED DIMENSIONS ONLY.	
SHEET	A-5		